



ProLite P1905S-B2

19" LCD monitor with LED-backlit and protective glass

The ProLite P1905S meets the increasing demands for Protected LCD's within Education, Retail and Industrial applications. In addition to having toughened safety glass fitted behind the bezel at 8H hardness rating capable of resisting above normal impacts to the display, iiyama have enhanced the range to include the latest high performance and energy saving technology. Features include 5msec response time, 1000:1 contrast ratio enhancing colour and Analogue and DVI inputs. The displays are Energy Star® rated and have 19W typical power consumption in use and less than 1W in standby.

DISPLAY CHARACTERISTICS

| | |
|-------------------------|---|
| Diagonal | 19"; 48cm |
| Panel | TN LED |
| Glass thickness | 2 mm |
| Glass transmission rate | 96% up typical |
| Glass hardness | 8H minimum |
| Display area h x w | 301 x 376.3 mm; 11.9" x 14.8" |
| Response time | 5 ms |
| Contrast | 1000 : 1 typical |
| Brightness | 240 cd/m ² typical |
| Brightness | 300 cd/m ² max. |
| Viewing zone | horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 70° |
| Viewing zone CR>5 | horizontal/vertical: 170° / 170°; right/left: 85° / 85°; up/down: 85° / 85° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.294 x 0.294 mm |
| Native resolution | 1280 x 1024 (1.3 megapixel) |
| Horizontal sync | 30 - 80 KHz |
| Vertical sync | 55 - 75 Hz |
| Synchronization | Separate Sync |
| Aspect ratio | 5 : 4 |

POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 16 W typical; max. 0.5 W in Power management mode |
| Power management | VESA DPMS, ENERGY STAR® |

DIMENSIONS & WEIGHT

| | |
|----------------------|--------------------------|
| Dimensions w x h x d | 414.5 x 420.5 x 200.5 mm |
| Weight | 4.6 kg |

INTERFACES & CONNECTORS

| | |
|-------------------------|-------|
| Analog input connector | VGA |
| Digital input connector | DVI-D |
| HDCP | yes |

SPECIAL FEATURES

| | |
|-------------------|---|
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Plug & Play | VESA DDC2B™ |
| Controls | Via OSD in 9 languages (EN, FR, DE, NL, PL, RU, JP, Chinese - traditional and simplified) and 5 front controls (Power, Select / Input, Scroll up / Audio, Scroll down / i-Style Colour, Menu) |
| User controls | auto image adjust, picture adjust (contrast, brightness, ACR, ECO), input select, audio adjust (volume, mute), colour adjust, information, manual image adjust (H/V position, clock, phase, sharpness), setup menu (language select, OSD position, OSD timeout, OSD background, opening logo, LED), memory recall |
| Speakers | 2 x 1 W (Stereo) |
| Anti-theft-device | Kensington-lock™ prepared |
| Certificates | CE, TÜV-GS, CU |
| Tilt angle | 20° up; ° down |
| VESA mounting | 100 x 100 mm |
| Colour | Black |

ACCESSORIES

| | |
|----------------------|---|
| Driver | Windows 95/98/2000/ME/XP/Vista/7/8 |
| Included accessories | power cable, VGA (D-Sub) cable, DVI-D signal cable, audio cable, stand, quick start guide, safety guide |