



## ProLite E2273HDS-GB1

The ProLite E2273HDS is a LED-backlit monitor. It is a full 1920x1080 high definition 21.5" display that features all the benefits this technology affords. Extremely slim and stylish in design, it has a narrow bezel and is finished in the latest glossy-black. The high specifications of the monitor include 5,000,000:1 ACR, fast 2ms response for excellent sharpness in high definition video and triple input connectivity (including HDMI). Power consumption is only 21W typical usage and 0,5W in standby.

### DISPLAY CHARACTERISTICS

Diagonal	21.5"; 55 cm
Panel	TN LED-Backlit
Display area h x w	268.1 x 476.6 mm; 10.6" x 18.8"
Response time	2 ms
Contrast	1000 : 1 typical
Contrast	12 000 000 : 1 ACR
Brightness	250 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 ( 2.1 megapixel)
Horizontal sync	24 - 83 KHz
Vertical sync	55 - 76 Hz
Synchronization	Separate sync
Aspect ratio	16 : 9

### POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	24 W typical; max. 0,5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

### EU ENERGY EFFICIENCY LABEL

Energy efficiency class	B
On Mode Power Consumption	21.4W
Annual Energy Consumption	31 kW/annum*
Visible Screen Diagonal	51 cm; 22"

This is information under Regulation (EU) No 1062/2010.

\*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.

### EPEAT SILVER

**EPEAT** EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit [www.epeat.net](http://www.epeat.net) for the registration status in your country.

### INTERFACES & CONNECTORS

Analog input connector	VGA
Digital input connector	DVI-D, HDMI
HDCP	yes

### SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2B™
Controls	Via OSD in 8 languages (EN, DE, FR, ES, IT, FIN, Chinese, JP) and 5 front controls (Power, Select/ Input Select, Scroll up/ Audio, Scroll down/ i-style Colour, Menu)
User controls	auto adjust, luminance (contrast, brightness, ECO, ACR, OD), input select, audio adjust (volume, mute, HDMI audio), colour adjust, information, image steep (clock, H. position, V. position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, LED), recall
Speakers	2 x 1 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Certificates	TCO5.2, CE, CB, FCC-B, TUV-Bauart, VCCI-B, PSE
Tilt angle	20° up; 5° down
VESA mounting	100 x 100 mm
Colour	Black

### ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Included accessories	power cable, DVI-D cable, audio cable, cable holder, stand, quick start guide, safety guide

### DIMENSIONS & WEIGHT

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

Dimensions w x h x d	506.5 x 390 x 178 mm
Weight	3.3 kg