

ProLite T2236MSC-B1

22" 10 point touch monitor with edge-to-edge glass and AMVA panel

With its Full HD (1920x1080) resolution and accurate Projective Capacitive 10 point touch technology, the ProLite T2236MSC delivers seamless and accurate touch response. The AMVA panel technology guarantees high performance with excellent colour reproduction and high contrast, making it an excellent choice for a vast array of demanding interactive applications. The flexible stand can be positioned at several angles, or laid flat on a surface, creating a comfortable and ergonomic user experience. The ProLite T2236MSC is the ideal screen for a great Windows8 touch-experience.



DISPLAY CHARACTERISTICS

| | |
|---------------------|---|
| Diagonal | 21.5" |
| Touchtechnology | projective capacitive, multitouch (10 compatible touch points - HID, only with supported OS), activated by finger |
| Panel | AMVA LED |
| Display area h x w | 476.6 x 268.1 mm; 18.8" x 10.6" |
| Response time | 12 ms |
| Contrast | 3 000 : 1 with touch panel |
| Brightness | 225 cd/m ² with touch panel |
| Viewing zone | horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.248 x 0.248 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 30 - 80 KHz |
| Vertical sync | 56 - 75 Hz |
| Synchronization | Separate Sync |
| Aspect ratio | 16 : 9 |
| Light transmittance | 90% |

POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 23 W typical; max. 0.5 W in Power management mode |
| Power management | VESA DPMS |

DIMENSIONS & WEIGHT

| | |
|----------------------|------------------------------|
| Dimensions w x h x d | 522.5 x 128 (385) x 238.5 mm |
| Weight | 6.6 kg |

INTERFACES & CONNECTORS

| | |
|-------------------------|--|
| Analog input connector | VGA (D-Sub) |
| Digital input connector | DVI-D, HDMI |
| Headphone connector | Yes |
| Inputs | USB (for touch connectivity), USB 3.0 VGA, DVI-D, HDMI, USB HUB |
| USB hub | UP 1 x USB 3.0 / DOWN 4 x USB 3.0 |

SPECIAL FEATURES

| | |
|-------------------------|--|
| Plug & Play | VESA DDC2BT TM |
| Controls | On-Screen-Display in 9 languages (EN, FR, DE, ES, IT, PT, RU, JP, Chinese simplified) and 5 front controls (Scroll up / Audio Adjust button, Scroll down / ECO button, Auto button, Menu button, Power switch) |
| User controls | luminance (contrast, brightness, ECO, i-Style colour, ACR), image setup (clock, phase, H.position, V.position, aspect), colour temp., OSD setup (H.position, V. position, timeout, language), extra (reset, signal select, HDMI audio, OD, information), volume, auto adjust |
| Speakers | 2 x 2 W (Stereo) |
| Anti-theft-device | Kensington-lock TM prepared |
| Safety | CE, TÜV-Bauart, CU |
| Height adjustable stand | Yes |
| Height adjustment | 257 mm |
| Tilt angle | 90° up; 5° down |
| VESA mounting | 100 x 100 mm |
| Colour | Black |

ACCESSORIES

| | |
|----------------------|--|
| Driver | multi-touch: Windows7/8 (HID compliant) |
| Included accessories | power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, quick start guide, safety guide |